

THC-T120-PC 2 MP Indoor Fixed Turret Camera



- 1080p turret camera
- Smart IR, up to 20 m IR distanceWater resistant (IP66)
- 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)

▪ Specification





Interface	
Video Output	1 HD analog output
Switch Button	TVI/AHD/CVI/CVBS
Selection Parameter	
Case Type	Turret
WDR	DWDR
Length Type	Fixed Lens
IR Distance	<30m
Power Supply	DC12V
Protection Level	N/A
Resolution	1080P
Video Output	4 in 1
Menu	
Day/Night Mode	IR cut filter
DWDR (Digital Wide Dynamic Range)	Support
Language	English
Functions	Brightness, Sharpness, DNR, Mirror, Smart IR
Backlight Compensation	Support
Camera	
Image Sensor	2 MP CMOS image sensor
Signal System	PAL/NTSC
Frame Rate	PAL: 1080p@25fps NTSC: 1080p@30fps
Resolution	1920 (H) × 1080 (V)
Shutter Time	1/25 (1/30) s to 1/50,000 s
Min. illumination	0.02 Lux@(F2.0, AGC ON), 0 Lux with IR
Lens	2.8 mm, 3.6 mm
Horizontal Field of View	2.8 mm, horizontal FOV: 96.5°, vertical FOV: 48.9°, diagonal FOV: 120.5° 3.6 mm, horizontal FOV: 76.9°, vertical FOV: 40.6°, diagonal FOV: 92.0°
Lens Mount	M12
Day & Night	IR cut filter
Synchronization	Internal synchronization
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 75°, Rotation: 0° to 360°
General	
Power Supply	12 VDC ± 15%
Power Consumption	Max. 2.1 W
Material	Plastic
IR Range	Up to 20 m
Dimensions	∅ 85.4 mm × 76.12 mm (∅ 3.38" × 2.67")
Weight	130 g (0.29 lb.)
Operating Conditions	-40 °C to 60 °C (-40 °F to 140 °F), Humidity: 90% or less (non-condensation)

▪ **Available Model**

THC-T120-PC

▪ **Accessory**

▪ **Optional**

HIA-J101 Junction Box	HIA-B201 Corner Mount	HIA-B301 Vertical Pole Mount	HIA-B401-110T Wall Mount
			

HiLook

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
Technical Support: support@hikvision.com

Follow us on social media to get the latest product and solution information.

